

# HO-400 / HO-400R INDIRECT FIRED HEATER



## INFORMATION SHEET

### FEATURES

- **Versatile Fuel Options**  
Diesel, Oil, or Kerosene Compatibility
- **Secure Containment**  
110% Steel Secondary Containment
- **Durable Heat Exchanger**  
Fully Welded 16 ga 304 Stainless Steel
- **Robust Body Panels**  
16 ga Carbon Steel with Chip-Resistant Coating
- **Reliable Mobility**  
Flat-Free Tires with Reinforced Hubs
- **Flexible Fuel Capacity**  
Optional 60 or 118 US gal (227 or 447 l) fuel tanks
- **High-Quality Burner**  
Equipped with Riello Burner



### SPECIFICATIONS

|                           | HO-400                                    | HO-400R                                   |
|---------------------------|-------------------------------------------|-------------------------------------------|
| <b>BTUH</b>               | 325,000 - 390,000 BTUH<br>95 - 114 kW     | 325,000 - 390,000 BTUH<br>95 - 114 kW     |
| <b>Air Movement</b>       | 2,400 CFM<br>68 m <sup>3</sup> /min       | 3,500 CFM<br>99 m <sup>3</sup> /min       |
| <b>Weight</b>             | 580 lbs<br>263 kg                         | 600 lbs<br>272 kg                         |
| <b>Dimensions</b>         | 70" x 30" x 52"<br>178 x 76 x 132 cm      | 70" x 30" x 55"<br>178 x 76 x 140 cm      |
| <b>Power Supply</b>       | 120 V / 15 A                              | 120 V / 15 A                              |
| <b>Current Draw</b>       | 9 A                                       | 8 A                                       |
| <b>Ducting Capability</b> | 50' max<br>15 m max                       | 100' max<br>30 m max                      |
| <b>Recirculating</b>      | No                                        | Up to 50'<br>Up to 15 m                   |
| <b>Certification</b>      | cETLus                                    | cETLus                                    |
| <b>Fuel Tank Capacity</b> | 48 US gal<br>182 l                        | 48 US gal<br>182 l                        |
| <b>Run Time</b>           | 16 hrs @ 3 gal / hr<br>16 hrs @ 11 l / hr | 16 hrs @ 3 gal / hr<br>16 hrs @ 11 l / hr |
| <b>Fan Power</b>          | 3/4 hp<br>0.55 kW                         | 1 hp<br>0.74 kW                           |
| <b>Thermostat</b>         | Yes                                       | Yes                                       |